

# QSB5-G7

Emissions Compliance:  
EU Stage IIIA at 50Hz and 60Hz  
EPA Tier 4i at 50Hz and 60Hz



> Specification sheet

Our energy working for you.™



## Description

The QSB5 engine meets U.S. EPA Tier 4 Interim and EU Stage IIIA generator set emission standards with the proven 4.5-litre engine platform and a fully integrated system from air-intake to exhaust aftertreatment.

The exhaust aftertreatment consists of a Cummins Compact Catalyst that is maintenance free and space efficient. This catalyst only aftertreatment system simplifies operator interface and maximizes installation flexibility.

The four-cylinder QSB5 engine is ideally suited to both open and containerized applications in stationary or portable generator equipment. It can be matched to meet specific duty cycle and operating conditions of any generator.



This engine has been built to comply with CE certification.



This engine has been designed in facilities certified to ISO9001 and manufactured in facilities certified to ISO9001 or ISO9002.

## Features

**Cummins Compact Catalyst** – Very low PM emissions is achieved using the Cummins Compact Catalyst exhaust aftertreatment. The system is maintenance-free and offers a space-efficient installation profile. Cummins proven EGR system is utilized for NOx reduction.

**Full-Authority Electronic Controls** - Optimize engine operation and deliver critical information for controlling costs, reducing maintenance and seamless integration with other components.

**Variable Flow Turbocharger** – Electronic controlled single turbo for enhanced air management.

**Direct Flow Air Filtration System** - Provides up to 35% smaller, more flexible installation package and higher air filtration efficiency than radial air filters.

**Integrated Design** – Each component (Engine, Catalyst and Air Cleaner) has been specifically developed and rigorously tested for G-Drive products, ensuring high performance, durability and reliability.

**Service and Support** - G-Drive products are backed by an uncompromising level of technical support and after sales service, delivered through a world class service network.

## 1500 rpm (50 Hz Ratings)

Gross Engine Output			Typical Generator Set Output					
Standby	Prime	Base	Standby (ESP)		Prime (PRP)		Base (COP)	
kWm/BHP			kWe	kVA	kWe	kVA	kWe	kVA
72/97	63/84	57/76	53	66	48	60	44	55

## 1800 rpm (60 Hz Ratings)

Gross Engine Output			Typical Generator Set Output					
Standby	Prime	Base	Standby (ESP)		Prime (PRP)		Base (COP)	
kWm/BHP			kWe	kVA	kWe	kVA	kWe	kVA
86/115	75/100	67/90	60	75	54	68	50	62

Our energy working for you.™

[www.cumminsgdrive.com](http://www.cumminsgdrive.com)

©2012 | Cummins G-Drive Engines | Specifications Subject to Change Without Notice | Cummins is a registered trademark of Cummins Inc. S-1672 (7/12)



## General Engine Data

Type	4-cycle, in-line, 4-cylinder diesel
Bore	107 mm (4.21 in.)
Stroke	124 mm (4.88 in.)
Displacement	4.5 litre (272 in. <sup>3</sup> )
Cylinder Block	Cast iron, 4 cylinder
Battery Charging Alternator	100 amps
Starting Voltage	12 volt, negative ground
Fuel System	Direct injection
Fuel Filter	Spin on fuel filters with water separator
Lube Oil Filter Type(s)	Spin on full flow filter
Lube Oil Capacity	12.1 litre (12.8 qt)
Flywheel Dimensions	SAE3 / 11.5"

## Ratings Definitions

### Emergency Standby Power (ESP):

Applicable for supplying power to varying electrical load for the duration of power interruption of a reliable utility source. Emergency Standby Power (ESP) is in accordance with ISO 8528. Fuel Stop power in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.

### Limited-Time Running Power (LTP):

Applicable for supplying power to a constant electrical load for limited hours. Limited-Time Running Power (LTP) is in accordance with ISO 8528.

### Prime Power (PRP):

Applicable for supplying power to varying electrical load for unlimited hours. Prime Power (PRP) is in accordance with ISO 8528. Ten percent overload capability is available in accordance with ISO 3046, AS 2789, DIN 6271 and BS 5514.

### Base Load (Continuous) Power (COP):

Applicable for supplying power continuously to a constant electrical load for unlimited hours. Continuous Power (COP) in accordance with ISO 8528, ISO 3046, AS 2789, DIN6271 and BS 5514.

## Engine Weight & Dimensions (excluding Air Cleaner & Catalyst)

Length	Width	Height	Weight (dry)
mm	mm	mm	kg
865	720	941	371

## Fuel Consumption 1500 (50 Hz)

%	kWm	BHP	L/ph	US gal/ph
<b>Standby Power</b>				
100	72	97	19	5.0
<b>Prime Power</b>				
100	63	84	17	4.5
75	47	63	13	3.4
50	31	42	9	2.3
25	16	21	6	1.5
<b>Continuous Power</b>				
100	57	76	15	3.9

## Fuel Consumption 1800 (60 Hz)

%	kWm	BHP	L/ph	US gal/ph
<b>Standby Power</b>				
100	86	115	22	5.7
<b>Prime Power</b>				
100	75	100	19	5.1
75	56	75	15	4.0
50	37	50	11	2.8
25	19	25	6	1.7
<b>Continuous Power</b>				
100	67	90	17	4.6

## Cummins G-Drive Engines

### Asia Pacific

10 Toh Guan Road  
#07-01  
TT International Tradepark  
Singapore 608838  
Phone 65 6417 2388  
Fax 65 6417 2399

### Europe, CIS, Middle East and Africa

Manston Park Columbus Ave  
Manston Ramsgate  
Kent CT12 5BF. UK  
Phone 44 1843 255000  
Fax 44 1843 255902

### Latin America

Rua Jati, 310, Cumbica  
Guarulhos, SP 07180-900  
Brazil  
Phone 55 11 2186 4552  
Fax 55 11 2186 4729

### Mexico

Cummins S. de R.L. de C.V.  
Eje 122 No. 200 Zona Industrial  
San Luis Potosí, S.L.P. 78090  
Mexico  
Phone 52 444 870 6700  
Fax 52 444 870 6811

### North America

1400 73rd Avenue N.E.  
Minneapolis, MN 55432  
USA  
Phone 1 763 574 5000  
USA Toll-free 1 877 769 7669  
Fax 1 763 574 5298

Our energy working for you.™

[www.cumminsgdrive.com](http://www.cumminsgdrive.com)

©2012 | Cummins G-Drive Engines | Specifications Subject to Change Without Notice | Cummins is a registered trademark of Cummins Inc.  
S-1672 (7/12)

